



B-064.201L(B-064-1)

| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|---------------------------|------|------|-----------|------|
| 1 | CANCEL(T); UPDATE DRAWING | | | | |
| | | | | | |

| | | | | | |
|--|--------------|------------------------|-----------------|---------------------------|---------|
| DRAWN & DRAFTED BY WANG CHENG | TOLERANCES | | ANGLE: | TITLE: | |
| | 0<L≤4 ±0.1 | COPLANARITY 0.1 MAX | ±1° | SMD BOBBIN EE-6.3 (2 SEC) | |
| CHECKED & APPROVED BY CHIN TE | 4<L≤16 ±0.2 | | UNIT: | BOBBIN MATERIAL: | UL REC. |
| | 16<L≤63 ±0.3 | MM | LCP E4008 | UL 94V-0 | |
| PIN SHINE INDUSTRIAL CO., LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | ORIGIN: | PIN MATERIAL: | PIN TENSION LOAD: | |
| | | DG | PHOSPHOR BRONZE | 1.0KG MIN | |
| | | | DATE: | DRAWING NO. | REV. |
| | | | APR.02 '2003 | S-605 | 1 |