



B-052.101P (B-052)

| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|---|------|------|-----------|------|
| 1 | CANCEL (R),(P),(B2)(N); PIN TENSION LOAD 1.0KG-->1.5KG; | | | | |
| | UPDATE DRAWING | | | | |

| | | | | | |
|---|--------------|------------------------|-----------------|--------------------------|---------|
| DRAWN & DRAFTED BY ZHANG ZHI QIANG | TOLERANCES | | ANGLE: | TITLE: | |
| | 0<L≤4 ±0.1 | COPLANARITY 0.1 MAX | ±1° | C TYPE SMD BOBBIN EFD-20 | |
| CHECKED & APPROVED BY JOHN RONG | 4<L≤16 ±0.2 | | UNIT: | BOBBIN MATERIAL: | UL REC. |
| | 16<L≤63 ±0.3 | MM | PHENOLIC PM9630 | UL 94V-0 | |
| PIN SHINE INDUSTRIAL CO., LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | ORIGIN: | PIN MATERIAL: | PIN TENSION LOAD: | |
| | | DG | PHOSPHOR BRONZE | 1.5KG MIN | |
| | | | DATE: | DRAWING NO. | REV. |
| | | | APR.28 '2003 | S-2003 | 1 |