



| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|---|------|------|-----------|------|
| 1 | CHANGE PIN TENSION LOAD FROM 1.5KG TO 1.0KG MIN | | | | |
| 2 | CANCEL (D),(Q); PIN TENSION LOAD 1.0KG->1.5KG; | | | | |
| | UPDATE DRAWING | | | | |

| | | | | | |
|--|--------------|------------------------|-----------------|-------------------|---------|
| DRAWN & DRAFTED BY YAN WEI MING | TOLERANCES | | ANGLE: | TITLE: | |
| | 0<L≤4 ±0.1 | COPLANARITY 0.1 MAX | ±1° | SMD BOBBIN EPC-19 | |
| CHECKED & APPROVED BY ZHONG YU | 4<L≤16 ±0.2 | | UNIT: | BOBBIN MATERIAL: | UL REC. |
| | 16<L≤63 ±0.3 | MM | PHENOLIC PM9820 | UL 94V-0 | |
| PIN SHINE INDUSTRIAL CO.,LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | ORIGIN: | PIN MATERIAL: | PIN TENSION LOAD: | |
| | | DG | PHOSPHOR BRONZE | 1.5KG MIN | |
| | | DATE: | DRAWING NO. | REV. | |
| | | APR.04 '2003 | S-1901 | 2 | |