



| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|--|------|------|-----------|------|
| 1 | PIN TENSION LOAD 1.0KG-->1.5KG; UPDATE DRAWING | | | | |
| | | | | | |
| | | | | | |

| | | | | | | | |
|--|--------------|---|------------------------|---|-------------------------------------|---------------------------------|-----------|
| DRAWN & DRAFTED BY | ZHANG CHAO | TOLERANCES | | ANGLE: $\pm 1^\circ$ | TITLE: SMD BOBBIN ER-10/2 | | |
| | | 0<L≤4 ±0.1 4<L≤16 ±0.2 16<L≤63 ±0.3 | COPLANARITY 0.1 MAX | | | | |
| CHECKED & APPROVED BY | TIAN BAI SEN | | | UNIT: MM | BOBBIN MATERIAL: PHENOLIC PM9630 | UL REC. UL 94V-0 | |
|  PIN SHINE INDUSTRIAL CO.,LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | | | ORIGIN: SZ | PIN MATERIAL: PHOSPHOR BRONZE | PIN TENSION LOAD: 1.5KG MIN. | |
| | | | |  | DATE: APR.28 '2003 | DRAWING NO. S-1010 | REV. 1 |