



REV.	REVISIONS	REC.	REV.	REVISIONS	REC.
1	PIN LOAD 1.5KG CHANGE TO 2.0KG		5	PIN WIND 0.6 AND 1.0 TOLERANCES ±0.05MM,(B)24.0±0.15mm	
2	(K)14.40mm CHANGE TO 14.4+0.02/-0.15mm.			CHANGE TO 24.0 ± 0.10MM	
4	(P)0±0.10mm CHANGE TO 0.15±0.10mm.				

DRAWN & DRAFTED BY ZHANG CHAO	TOLERANCES		ANGLE: ±1°	TITLE: SMD BOBBIN UI-15 (8 SEC)	
	0<L≤4 ±0.1	COPLANARITY 0.1 MAX	UNIT: MM	BOBBIN MATERIAL: LCP E4008	UL REC. UL 94V-0
CHECKED & APPROVED BY TIAN BAI SEN	4<L≤16 ±0.2		ORIGIN: SZ	PIN MATERIAL: PHOSPHOR BRONZE	PIN TENSION LOAD: 2.0KG MIN.
PIN SHINE INDUSTRIAL CO.,LTD. TEL:886-2-22990545 FAX:886-2-22990546			DATE: MAR.08 '2002	DRAWING NO. S-1506	REV. 5