



NOTE:

PIN PULL-OUT FORCE SHOULD BE
0.8kg MIN. BEFORE SOLDERING
1.2kg MIN. AFTER SOLDERING

| REV. | REVISIONS | REC. | DATE | REV. | REVISIONS | REC. | DATE |
|------|--------------------|------|------|------|-----------|------|------|
| 1 | ADD NOTE | | | | | | |
| 2 | (G): 4.2 → 4.3±0.1 | | | | | | |

| | | | | | | | | |
|--|-----------|--------------|-------------------|--------|----------------------|-----------------|---------|-------------------|
| DRAWN & DRAFTED BY | SAND WANG | TOLERANCES | | ANGLE: | TITLE: | | | |
| | | 0<L≤4 ±0.1 | pin pitch ±0.2 | ±1° | T-H BASE 10.1X8.75X5 | | UL REC. | |
| CHECKED & APPROVED BY | JOHN RONG | 4<L≤16 ±0.2 | | UNIT: | BOBBIN MATERIAL: | DAP AM113 | | UL 94-V0 |
| | | 16<L≤63 ±0.3 | ORIGIN: | MM | PIN MATERIAL: | PHOSPHOR BRONZE | | PIN TENSION LOAD: |
| PIN SHINE INDUSTRIAL CO.,LTD. TEL:886-2-22990545 FAX:886-2-22990546 | | | DG | | DATE: | DRAWING NO. | REV. | |
| | | | | | OCT.04 '2002 | PB-022 | 2 | |