



| REV. | REVISIONS | REC. | REV. | REVISIONS | REC. |
|------|-----------|------|------|-----------|------|
|      |           |      |      |           |      |
|      |           |      |      |           |      |
|      |           |      |      |           |      |

|                                       |              |                          |                |                                |         |
|---------------------------------------|--------------|--------------------------|----------------|--------------------------------|---------|
| DRAWN & DRAFTED BY<br>WU FANG         | TOLERANCES   |                          | ANGLE:         | TITLE:                         |         |
|                                       | 0<L≤4 ±0.1   | pin pitch<br>±0.2        | ±1°            | T-H BOBBIN BE-16H (2 SEC)      |         |
| CHECKED & APPROVED BY<br>TIAN BAI SEN | 4<L≤16 ±0.2  |                          | UNIT:          | BOBBIN MATERIAL:               | UL REC. |
|                                       | 16<L≤63 ±0.3 | MM                       | PHENOLIC T375J | UL 94V-0                       |         |
| ORIGIN:<br>DG SZ                      |              | PIN MATERIAL:<br>CP WIRE |                | PIN TENSION LOAD:<br>1.5KG MIN |         |
| DATE:<br>SEP.06 '1995                 |              | DRAWING NO.<br>P-1609    |                | REV.<br>0                      |         |



PIN SHINE INDUSTRIAL CO.,LTD.

TEL:886-2-22990545

FAX:886-2-22990546

